Composites Science and Technology **29** (1987) 323–324

SUBJECT INDEX TO VOLUME 29

APC2 (carbon/PEEK), 2
Ageing (temperature dependence), 79
Anisotropy (flow-induced), 89
Aramid composites, 161
Axial shear (ud composites), 116, 123
Axisymmetric analysis, 110

Bearing stiffness (in joints), 59
Bend-tests, 92
Bolted joints (fatigue), 45

CFRP, 257
  bolted joints (fatigue), 45
CSM glass/polyester composites, 79
CVD matrix composites, 239
Carbon/carbon composites, 239
Carbon/Kevlar hybrids, 161
Carbon/PEEK composites, 1
Carbon fibre precursor (structure), 33
Carbon fibre/phenolic composites, 189, 211
Compliance calibration, 23
Constraint (in joints), 63
Correction factor (finite width), 141
Crack
  growth, 17
    resistance, 26
  modelling, 139
Cylindrical bending (shells), 169

Damage (fatigue in bolted joints), 49
Delamination fatigue cracks, 273
Dynamic mechanical analysis (DMA), 239

Elliptical holes in laminates, 133
End notch flexure test (ENF), 3
ENF (finite element analysis), 5
Equal rank assumption (fatigue life), 269
Exact solutions (cylindrical shells), 169

FPF criterion, 138
Fatigue
  (CFRP), 257, 266, 273
    (bolted joints), 45
  crack propagation, 284
  cracks (delamination), 273
  damage, 266
Fibre failure strain, 257
Finite width correction, 141
Flexural properties (hybrid composites), 161
Fractography, 10, 31
Fracture
  criteria, 137
  mechanisms, 140, 144
  strength (notched composites), 133
  toughness, 23
    (interlaminar), 1

Composites Science and Technology (**29**) (1987)—© Elsevier Applied Science Publishers Ltd, England, 1987. Printed in Great Britain

Glass/epoxy composites, 19
Glass-filled polyester (moisture absorption), 293
Glass/polypropylene composites, 89

Hole elongation (in joints), 60
Hybrid composites, 161
Hygrothermal (hydrothermal) ageing, 79

Impact behaviour, 89, 95
Infra-red analysis, 35
Injection moulded composites, 89
Interlaminar fracture, 1

J-polymer composites, 161
Joint deformation, 62

Kevlar/carbon hybrids, 161
Kinetic energy effects (fracture), 6

Laminated cylindrical shells, 169

Matrix failure strain, 257
Microscopic analysis, 280
Minimum strength model, 138
Mode II shear fracture, 1, 6
Moisture absorption, 293
  (effect of stress), 301

Notch sensitivity, 146

Oxidative stabilization (of PAN), 33

PEEK composites, 1
Phenolic composites, 189, 211
Pin-loaded joints, 45
Pitch matrix composites, 239
Point strength model, 137
Polyacrylonitrile (PAN) fibres, 33
Polypropylene composites, 89

R-curves, 26
R-ratio (fatigue), 273
Rate sensitivity, 1
Residual stress calculation, 312

S/N curves (CFRP joints), 61
Shear displacement (mode II cracks), 6
Sheet moulding compound (SMC), 303
Short-fibre composites, 17, 89
Silica fibre/phenolic composites, 189, 211
Single edge notch tests, 19
Slippage (in bolted joints), 48
SMC (moisture absorption), 303
Strength of notched composites, 133
Strength prediction, 142
Stress
  analysis, 134
  intensity (fatigue), 277
  ratio (effect of fatigue), 273

Temperature loading, 123
Thermal conductivity
  (phenolic composites), 189, 211
  models, 211
Thermal diffusivity, 189, 211
Thermal expansion (ud composites), 127
Thermoviscoelastic behaviour, 103
Transverse shear, 119
Transverse uniaxial behaviour, 119

Unidirectional composites, 103, 107

X-radiography (fatigue damage), 266
X-ray scattering, 35